

View Online at <https://aerobasegroup.com/nsn/7035-01-520-6493>

**Operating Temperature Range:**

+0.0/+50.0 degrees celsius

**End Application:**

Ts2100 irig/ru (56738) , network time server

**Mounting Method:**

Rack

**Maximumlength:**

12.000 inches

**Maximumwidth:**

17.000 inches

**Maximumheight:**

1.750 inches

**Special Features:**

Product includes: tymserve 2100 network time server, two-year warranty, power cord, manual, mib ii software, sntp client software; stand-alone ntp time server; network management protocol; telnet and rs-232 remote access; independent time acquisition from: gps satellite, irig time code, dial-up time service; front panel display and keypad; irig b time code input/output, 1 pps ttl/cmos output, 10 mhz output, sysplex timer output; md5 access authentication for security; http status page; rubidium oscillator upgrade; front panel keypad: 0 to 9, menu; front panel display: lcd, 2 x 40 character; front panel indicators: led, locked, tracking, power; irig b time code input supports ieee-1344 leap second, year and time figure of merit enhancements; configuration is entered via the front panel keypad or the rs-232 remote programming port

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A31700