

View Online at <https://aerobasegroup.com/nsn/7035-01-527-2560>

**Special Features:**

Ibm chipset first generation xa-32; support configurations tw0-way, four-way and eight-way using one x440, 16-way smp using two x440 chassis; supported processors xeon mp 1.5 ghz, 1 mb l3, xeon mp 1.9 ghz, 1 mb l3, xeon mp 2.0 ghz, 2 mb l3, xeon dp 2.4 ghz, 512 mb l2, up to four-way smp only; xcel4 server accelerator cache 32 mb xcel 4 per four-way smp expansion module, 64 mb xcel 4 cache in eight-way configuration, 128 mb xcel 4 cache in 16-way configuration; memory capaci type 512 mb and 1 gb dimms supported, 2 gb dimms by special bid only; 16 gb ram maximum per smp expansion module, up to 32 gb ram, 64 gb in a 16-way

**Supplementary Features:**

Type of memory used pc 133 sdram memory and four-way interleaving; internal hard drive capacity two ultra 160 hard drive bays, drives up to 73 gb supported, 146 gb total; adaptec dual channel ultra 160 scsi, optional serveraid for internal drives and external drives; ethernet single port, broadcom bcm5700 10/100/1000 base-t; six activepci-x, hot-swap, adapter slots, all 64 bit two support 33 or 66 mhz adapters, two support 33, 66 or 100 mhz adapters, or one 133 mhz adapter and the other slot vacant, two support 33, 66, 100, or 133 mhz adapters; 24x cd-rom; video controller s3 savage 4, 8 mb; 4 u rack optimized

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A23900