## NSN 7050-00-531-1966

Digital To Analog Converter - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/7050-00-531-1966

_		_	
Cn.	acial	Engl	tures:
JU	ELIA	геа	iui es.

 $23 \ gold \ plated \ pin \ type \ contact, \ output \ current \ 2 \ ma, \ accuracy \ porm \ 0.5 \ pct, \ ripple \ 10 \ mv \ rms \ max, \ 2.00 \ in. \ Lg, \ 1.50 \ in. \ W, \ 0.670 \ in. \ Thk \ o/a \ accuracy \ porm \ 0.5 \ pct, \ ripple \ 10 \ mv \ rms \ max, \ 2.00 \ in. \ Lg, \ 1.50 \ in. \ W, \ 0.670 \ in. \ Thk \ o/a \ accuracy \ porm \ 0.5 \ pct, \ ripple \ 10 \ mv \ rms \ max, \ 2.00 \ in. \ Lg, \ 1.50 \ in. \ W, \ 0.670 \ in. \ Thk \ o/a \ accuracy \ porm \ 0.5 \ pct, \ ripple \ 10 \ mv \ rms \ max, \ 2.00 \ in. \ Lg, \ 1.50 \ in. \ W, \ 0.670 \ in. \ Thk \ o/a \ accuracy \ porm \ 0.5 \ pct, \ ripple \ 10 \ mv \ rms \ max, \ 2.00 \ in. \ Lg, \ 1.50 \ in. \ W, \ 0.670 \ in. \ Thk \ o/a \ accuracy \ porm \ 0.5 \ pct, \ ripple \ 10 \ mv \ rms \ max, \ 2.00 \ in. \ Lg, \ 1.50 \ in. \ W, \ 0.670 \ in. \ Thk \ o/a \ accuracy \ porm \ 0.5 \ pct, \ ripple \ 10 \ mv \ rms \ max, \ 2.00 \ in. \ Lg, \ 1.50 \ in. \ W, \ 0.670 \ in. \ Thk \ o/a \ accuracy \ porm \ 0.5 \ pct, \ ripple \ 10 \ mv \ rms \ max, \ 2.00 \ in. \ Lg, \ 1.50 \ in. \ W, \ 0.670 \ in. \ Thk \ o/a \ accuracy \ porm \ 0.5 \ pct, \ ripple \ 10 \ mv \ rms \ max, \ 2.00 \ in. \ Lg, \ 1.50 \ in. \ Porm \ pct, \$ 

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A508I0