

View Online at <https://aerobasegroup.com/nsn/7310-01-102-6731>

Maximum Operating Pressure:

15.0 pounds per square inch

Current Type:

Ac

Frequency Rating:

60.0 hertz

Compartment Quantity:

1

Insulated Feature:

Included

Lining Material:

Aluminum

Voltage Rating:

440.0 pounds per hour wet

Exhaust Type:

Open

Heating Method:

Electrical

Wattage Rating:

8.0 kilowatts

Steam Supply System For Which Designed:

Self-contained steam generator

Exterior Shell Material:

Steel, corrosion resisting

Err Default:

Err default

Err Default:

Err default

Err Default:

Err default

Err Default:

Err default

Err Default:

Err default

Err Default:

Err default

Phase:

Three

Special Features:

Navy apl 432410028 applies; includes flange counter feet; marine wiring; pans, 6 each, 2 1/2 in perforated; water retainer; spray hose; step-down transformer; weight 143 lbs

Supplementary Features:

SPEC-IF-ICN-SNRE

Specification Or Standard:

1-3c size and a style and iii type

Departure From Cited Document:

Nsu approved/navsea nswccd, 4march2005

Departure From Cited Designator:

As modified by voltage rating; for naval shipboard use

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T281-k