

View Online at <https://aerobasegroup.com/nsn/7320-01-257-4176>

Mounting Type:

Floor

Current Type:

Ac

Frequency Rating:

60.0 hertz

Interval Timer:

Included

Furnished Items:

1 ea 40 and 80 qt stls stl bowls, 1 ea 40 and 80 qt stls stl and/or alum alloy batter beaters, sweet dough beaters, dough hooks, pastry knives, wing and wire whips, dollies, 40 qt bowl adapter, 80 qt bowl extension, hub drive and must be o/a stls stl construction

Voltage Rating:

440.0 volts

Accommodated Bowl Capacity:

40.0 quarts and 80.0 quarts

Bowl Quantity:

1 and 1

Bowl Capacity Range:

+40.0 to 46.0 quarts and +80.0 to 90.0 quarts

Bowl Material:

Steel, stainless and steel, stainless

Dolly Quantity:

1 and 1

Bowl Capacity Accommodated:

40.0 quarts and 80.0 quarts

Phase:

Three

Special Features:

For naval shipboard installation design w/capability of passing through 26 in. By 66 in. Hatch and must be o/a stls stl construction

Material:

Aluminum alloy 3003

Supplementary Features:

SPEC-IF-ICN-SNRE

Specification Or Standard:

li model and 80 size and 1 style

Departure From Cited Document:

Nsu approved/navsea, nswccd, 4 march 2005

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T281-c