

View Online at <https://aerobasegroup.com/nsn/7320-01-506-6287>

Current Type:

Ac

Frequency Rating:

60.0 hertz

Tank Type For Which Designed:

Double

Operational Direction:

Left-hand

Voltage Rating:

440.0 volts

Design Type:

Straight through

Feed Type:

Conveyor

Heating Method:

Electrical

Conveyor Type:

Chain

Product Name:

Champion upright conveyer dishwasher with external booster heater. Mdl. Usn72-135/electric.

Phase:

Three

Special Features:

Unit feed direction is left to right. Deep tank design can withstand 15-degree list and roll with out spilling. Saftey features: final rinse low temperature shutdown. Conveyer jam limit switch. Door saftey switch. Float operated low water level switch with a 5 second delay for pitch and roll.

Special Test Features:

Power requirements are 2 each 440v/60/3 50 amp supplies for the dishwasher and one each 440v/60/3 100 amp for the booster heater.

Supplementary Features:

Comes with a remote mounted nema 4x control cabinet. (9)tray/plat (type 1)/(14)cup/bowl(type2)/(2)cylinder transport rack(type3)/(12)plastic cylinder(type5)/(12)s/s cylinders(type6) .

Departure From Cited Document:

Nsu approved/navsea nswccd, 4march2005

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T281-h