

View Online at <https://aerobasegroup.com/nsn/7320-01-506-6296>

**Current Type:**

Ac

**Frequency Rating:**

60.0 hertz

**Tank Type For Which Designed:**

Double

**Operational Direction:**

Left-hand

**Voltage Rating:**

440.0 volts

**Design Type:**

Straight through

**Feed Type:**

Conveyor

**Heating Method:**

Electrical

**Conveyor Type:**

Chain

**Product Name:**

Champion upright conveyer dishwasher with external booster heater. Mdl. Usn72-250/electric.

**Phase:**

Three

**Special Features:**

Unit feed direction is left to right. Deep tank design can withstand 15-degree list and roll with out spilling. Saftey features: final rinse low temperature shutdown. Conveyer jam limit switch. Door saftey switch. Float operated low water level switch with a 5 second delay for pitch and roll.

**Special Test Features:**

Power requirements are 2 each 440v/60/3 50 amp supplies for the dishwasher and one each 440v/60/3 100 amp for the booster heater.

**Supplementary Features:**

Comes with a remote mounted nema 4x control cabinet. (9)tray/plat (type 1)/(14)cup/bowl(type2)/(2)cylinder transport rack(type3)/(12)plastic cylinder(type5)/(12)s/s cylinders(type6) .

**Departure From Cited Document:**

Nsu approved/navsea nswccd, 4march2005

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T281-h