

View Online at <https://aerobasegroup.com/nsn/7320-01-525-8183>

**Current Type:**

Ac

**Frequency Rating:**

60.0 hertz

**Voltage Rating:**

240.0 volts

**Design Type:**

Front door

**Feed Type:**

Manual

**Heating Method:**

Electrical

**Rack Quantity Per Hour:**

30

**Product Name:**

Undercounter dish machine in 208-240/60/1, 2w, with a detergent and rinse aid pump

**Phase:**

Single

**Special Features:**

Mstandard features hot water and chemical sanitation; low chemical alert indicator on machines ordered with pumps; 70 degrees f rinse booster heater on lxih models; delime notification/cycle; chemical pump auto prime; service diagnostics; fresh water rinse 1.2 gallons per rack; 16 guage stainless steel tank, door and top panel; microcomputer, top mounted controls with digital cycle/temperature display; revolving upper and lower anti-clogging wash arms; revolving upper and lower anti-clogging rinse arms; removable stainless steel scrap screen; corrosion resistant pump; automatic pumped drain; 17 inch door opening; automatic fill; labyrinth-type door seal; electric tank heat; two dishracks-one peg and one combination type

**Supplementary Features:**

Accessories power cord kits; stainless steel base with 6 inch legs; 17 inch stainless steel stand; pressure regular valve; rated amps 37.7; min supply ckt conduct ampaci type 50; maximum protective devices 50; shipping weights net weight of machine 210 lbs, domestic shipping weight 255 lbs; machine ratings 750 dishes per hr; 1080 glasses per hr; 3/4 hp wash motor; microcomputer controls; 3 gallon tank capacity; dimensions 33.750 x 23 15/16 x 26.750 inch; 2 minute cycle time; 1.5 kw tank heat; 6 kw electric booster heater; 1.2 gallon water usage per rack; pumped drain design; 17 inch door opening height; 10 gpm peak drain flow

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T281-h