

View Online at <https://aerobasegroup.com/nsn/7490-01-454-9822>

Overall Length:

480.0 millimeters

Overall Width:

275.0 millimeters

Fastener Holes:

Not included

Special Features:

Direct thermal and thermal printer for self adhesive labels, tickets and tags; non peel off function; (peel of internal rewind of backing paper is optional); label/ribbon roll: label roll 205mm maximum dia, ribbon roll 450m maximum length, bobbin diameter is 38-40mm and 75mm; software: printer language-ubi fingerprint, ubi direct protocol, windows label program: ubi labelshop; windows printer driver; characters: truedoc and truetype font capability; fonts are scalable; font cache for performance; 15 unicode scalable latin fonts; non-latin fonts for eastern europe, the middle east and asia are optional; most current bar code symbologies are on board, including 2d codes; prints smooth text, any size bar codes and graphics in all four directions; print resolution is 300dpi with easy inter-changeable magnetic quick-mount print head; operating temp 5 to 40 degrees centigrade; humidity type 20 to 40 percent non condensing

Material:

Aluminum and steel

Material:

Aluminum and steel

Supplementary Features:

Main: power factor correctio (pfc); mains switch automatically between 115v or 230vac, 45/65hz; voltage range: 90-264vac; memory: fast execution with new mips 32 bit risc processor; memory has 2mg flash, 4mb dram, 1 pc-card slot; real time clock; anti wrinkling system adjusts printer to the label and ribbon qualities; rs232, centronics interface, with 300-38400 baud rate; keyboard membrane switcheboard (0-9) and 13 other functions; display: back-lit lcd for 2x16 characters and a 3 led indicator; label size length: 400mm max; label width: 120mm max; print speed 100-300mm/s, (4-12 inches at 300dpi) , true speed equivalent to 30ppm, a4 at 300dpi; print width 106.6mm; name: easy coder 501xp

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T301-b