NSN 8010-01-293-0781

Polyurethane Coating - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/8010-01-293-0781

| Application Method: |
|--|
| Spraying as is |
| Quantity Within Each Unit Package: |
| 1.000 pints |
| Content Within Each Unit Package: |
| Consists of component a (pigmented polyester resin and solvent) and component b (clear aliphatic isocyanate) to equal 1 pint |
| Features Provided: |
| Lead free and chromate free |
| Gloss Designation: |
| Flat |
| Coloring Method: |
| Pigmented |
| Basic Formulation Type: |
| Polyurethane |
| Rated Drying Time: |
| 4.000 hours |
| Color Chip Number: |
| 36375 |
| Volatile Organic Compound In Grams Per Liter: |
| 340.0 |
| Environmental Attribute Code: |
| Low volatile organic compound - coatings - aerospace operations coatings |
| Special Features: |
| High solids; for ground support equipment |
| Color: |
| Gray |
| Specification Or Standard: |
| 2 type and h class |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A09700 |
| Mil-std (military Standard): |
| Mil-prf-85285 spec. |