## NSN 8010-01-380-0396

Polyurethane Coating - Page 1 of 1

Mil-prf-85285 spec.



View Online at https://aerobasegroup.com/nsn/8010-01-380-0396

| Specific Use:   |
|---|
| Aircraft surfaces   |
| Application Method:   |
| Spraying as is  |
| Quantity Within Each Unit Package:  |
| 2.000 gallons   |
| Content Within Each Unit Package:   |
| Consists of component a (pigmented polyester resin and solvent) and component b (clear aliphatic isocyanate) to equal 2 gallons |
| Features Provided:  |
| Lead free and chromate free   |
| Gloss Designation:  |
| Flat  |
| Coloring Method:  |
| Pigmented   |
| Basic Formulation Type:   |
| Polyurethane  |
| Rated Drying Time:  |
| 6.000 hours   |
| Color Chip Number:  |
| 30279   |
| Volatile Organic Compound In Grams Per Liter:   |
| 420.0   |
| Environmental Attribute Code:   |
| Low volatile organic compound - coatings - aerospace operations coatings  |
| Special Features:   |
| High solids   |
| Color:  |
| Brown   |
| Specification Or Standard:  |
| 1 type and h class  |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |
| Fiig:   |
| A09700  |
| Mil-std (military Standard):  |