## NSN 8010-01-423-3638

Polyurethane Coating - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/8010-01-423-3638

| ( | General purpose   |
|---|---|
| , | Application Method:   |
| ; | Spraying as is  |
| ( | Quantity Within Each Unit Package:  |
| 1 | 2.000 gallons   |
| ( | Content Within Each Unit Package:   |
| ( | Consists of component a (base) and component b (activator) to equal 2 gallo |
| I | Features Provided:  |
| I | Lead free and chromate free   |
| ( | Gloss Designation:  |
| I | Flat  |
| ( | Coloring Method:  |
| I | Pigmented   |
| I | Basic Formulation Type:   |
| I | Polyurethane  |
| I | Rated Drying Time:  |
| 1 | 2.000 hours   |
| ( | Color Chip Number:  |
| ; | 35450   |
| 1 | Volatile Organic Compound In Grams Per Liter:                               |
| 4 | 420.0   |
| I | Environmental Attribute Code:   |
| I | Low volatile organic compound - coatings - aerospace operations coatings    |
| ; | Special Features:   |
| ; | Self-priming topcoat  |
| ( | Color:  |
|   | Blue  |
|   | Shelf Life:   |
|   | N/a   |
| l | Unit Of Measure:  |
|   | -   |
|   | Demilitarization:   |
|   | No  |
|   | Fiig:   |
| 1 | A09700  |