## NSN 8010-01-486-7555

Epoxy Coating Kit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/8010-01-486-7555

| Application Method:  |
|--|
| Spraying after thinning or spraying as is  |
| Quantity Within Each Unit Package:   |
| 1.000 pints  |
| Content Within Each Unit Package:  |
| Component a and component b  |
| Features Provided:   |
| Chromate free  |
| Gloss Designation:   |
| Flat or lusterless   |
| Pigment Material Type:   |
| Rutile titanium dioxide and quinaroidone red and carbon black  |
| Vehicle Material Type:   |
| Epoxy resin and polyamide resin  |
| Finish For Which Formulated:   |
| Fine   |
| Rated Drying Time:   |
| 4.000 hours  |
| Color Chip Number:   |
| 31136  |
| Volatile Organic Compound In Grams Per Liter:  |
| 340.0  |
| Special Features:  |
| Pigment matl type, benzimidazolone yellow; quinacridone violet   |
| Color:   |
| Red  |
| Test Data Document:  |
| 81349-mil-c-22750 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain          |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).                            |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| Yes - demil/mli  |
| Fiig:  |
| A09700   |
| Mil-std (military Standard):   |
| Mil-c-22750 spec.  |