

View Online at <https://aerobasegroup.com/nsn/8010-01-486-7555>

**Application Method:**

Spraying after thinning or spraying as is

**Quantity Within Each Unit Package:**

1.000 pints

**Content Within Each Unit Package:**

Component a and component b

**Features Provided:**

Chromate free

**Gloss Designation:**

Flat or lusterless

**Pigment Material Type:**

Rutile titanium dioxide and quinacridone red and carbon black

**Vehicle Material Type:**

Epoxy resin and polyamide resin

**Finish For Which Formulated:**

Fine

**Rated Drying Time:**

4.000 hours

**Color Chip Number:**

31136

**Volatile Organic Compound In Grams Per Liter:**

340.0

**Special Features:**

Pigment matl type, benzimidazolone yellow; quinacridone violet

**Color:**

Red

**Test Data Document:**

81349-mil-c-22750 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A09700

**Mil-std (military Standard):**

Mil-c-22750 spec.