## NSN 8030-00-062-6950

Corrosion Preventive Compound - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/8030-00-062-6950

| Cold  Quantity Within Each Unit Package:   |
|--|
| Quantity Within Each Unit Package:   |
| additity Within Edon Office dokage.  |
| 1.000 quarts   |
| Usage Design:  |
| For protection of metals exposed to extended periods outdoors and for general purpose preservation, indoor or outdoor, with or without |
| cover, for domestic and overseas shipment where a dry-to-touch film is required  |
| Film Thickness:  |
| 0.004 inches   |
| Film Hardness Designation:   |
| Hard   |
| Melting Point Tempurature Rating:  |
| 175.0 degrees fahrenheit   |
| Features Provided:   |
| Petrolatum base and nontoxic   |
| Volatile Organic Compound In Grams Per Liter:  |
| 340.0  |
| Special Features:  |
| High voc; hard film; exceeds 340 grams per liter voc   |
| Supplementary Features:  |
| 1 quart can  |
| Specification Or Standard:   |
| 1 class and 1 grade  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| No   |
| Fiig:  |
| A535w0   |
| Mil-std (military Standard):   |
| Mil-c-16173 spec.  |
|  |