

View Online at <https://aerobasegroup.com/nsn/8030-01-476-2255>

Physical Form:

Pastepaste

Quantity Within Each Unit Package:

1.000 quarts1.000 quarts

Specific Usage Design:

For aircraft integral fuel tanks and fuel cell cavitiesfor aircraft integral fuel tanks and fuel cell cavities

Features Provided:

Separate catalyst

Rated Drying Time:

10.000 hours 10.000 hours

Volatile Organic Compound In Grams Per Liter:

46.046.0

Environmental Attribute Code:

Low volatile organic compound - household consumer productslow volatile organic compound - household consumer products

Special Features:

Service temperature range of minus 65 degrees f to plus 250 degrees f; for extrusion gun and spatula application; polysulfide; 1/2 hour working timeservice temperature range of minus 65 degrees f to plus 250 degrees f; for extrusion gun and spatula application; polysulfide; 1/2 hour working time

Material:

Rubber syntheticrubber synthetic

Supplementary Features:

24 fluid ounce base and required amount of curing agent in separate containers24 fluid ounce base and required amount of curing agent in separate containers

Specification Data:

81343-ams-s-8802 professional/industrial association standard81343-ams-s-8802 professional/industrial association standard

Specification Or Standard:

2 type and 2 type and b-1/2 classb-1/2 class

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A536d0