

View Online at <https://aerobasegroup.com/nsn/8030-01-656-7453>

Temperature Rating:

-40.0 degrees fahrenheit and 190.0 degrees fahrenheit

Physical Form:

Paste

Quantity Within Each Unit Package:

10.0 fluid ounces

Specific Usage Design:

Designed for marine applications above and below the waterline to include sealing fiberglass hulls, wood to fiberglass applications, porthole frames, deck fittings, moldings, thru hull and deck hardware

Curing Method:

Air dried

Content Within Each Unit Package:

10.0 fluid oz cartridge

Rated Drying Time:

Between 22.0 minutes and 24.0 hours

Product Name:

Marine adhesive/sealant fast cure 4000 uv

Special Features:

Less than 1% voc's, non-shrinking, non-sagging, non-corrosive, non-cracking, fast curing and paintable; superior uv resistance with exceptional sealing properties; coverage for 10 oz. Cartridge is 1/8" bead for 120 lineal feet; 38-39 shore a hardness rating; must be stored at 60-80 degrees f for storage life; when stored at the recommended conditions in the original, unopened container this product has a shelf life of 12 months from the date of shipment

Color:

White

Material:

Plastic polyurethane

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A536d0