

View Online at <https://aerobasegroup.com/nsn/8030-01-656-7453>

**Temperature Rating:**

-40.0 degrees fahrenheit and 190.0 degrees fahrenheit

**Physical Form:**

Paste

**Quantity Within Each Unit Package:**

10.0 fluid ounces

**Specific Usage Design:**

Designed for marine applications above and below the waterline to include sealing fiberglass hulls, wood to fiberglass applications, porthole frames, deck fittings, moldings, thru hull and deck hardware

**Curing Method:**

Air dried

**Content Within Each Unit Package:**

10.0 fluid oz cartridge

**Rated Drying Time:**

Between 22.0 minutes and 24.0 hours

**Product Name:**

Marine adhesive/sealant fast cure 4000 uv

**Special Features:**

Less than 1% voc's, non-shrinking, non-sagging, non-corrosive, non-cracking, fast curing and paintable; superior uv resistance with exceptional sealing properties; coverage for 10 oz. Cartridge is 1/8" bead for 120 lineal feet; 38-39 shore a hardness rating; must be stored at 60-80 degrees f for storage life; when stored at the recommended conditions in the original, unopened container this product has a shelf life of 12 months from the date of shipment

**Color:**

White

**Material:**

Plastic polyurethane

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A536d0