NSN 8040-00-185-5631

Adhesive - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/8040-00-185-5631

Physical Form: Film Quantity Within Each Unit Package: 50.000 square feet Specific Usage Design: For core splicing applications Features Provided: Heat vulcanize feature Special Features: 12 x 24 in. Sheet; 0.045 to 0.055 in. Thickness; foaming type; non-asbestos; cures at 250 or 350 degrees f; for service temperatures 350 degrees f; must be shipped and stored at 0 degrees f or below Material: Plastic epoxy Supplementary Features: 50 square foot Shelf Life: N/a Unit Of Measure: Demilitarization: No Filig:	No. of all Farms
Quantity Within Each Unit Package: 50.000 square feet Specific Usage Design: For core splicing applications Features Provided: Heat vulcanize feature Special Features: 12 x 24 in. Sheet; 0.045 to 0.055 in. Thickness; foaming type; non-asbestos; cures at 250 or 350 degrees f; for service temperatures 350 degrees f; must be shipped and stored at 0 degrees f or below Material: Plastic epoxy Supplementary Features: 50 square foot Shelf Life: N/a Unit Of Measure: Demilitarization: No	
50.000 square feet Specific Usage Design: For core splicing applications Features Provided: Heat vulcanize feature Special Features: 12 x 24 in. Sheet; 0.045 to 0.055 in. Thickness; foaming type; non-asbestos; cures at 250 or 350 degrees f; for service temperatures 350 degrees f; must be shipped and stored at 0 degrees f or below Material: Plastic epoxy Supplementary Features: 50 square foot Shelf Life: N/a Unit Of Measure: Demilitarization: No	
Specific Usage Design: For core splicing applications Features Provided: Heat vulcanize feature Special Features: 12 x 24 in. Sheet; 0.045 to 0.055 in. Thickness; foaming type; non-asbestos; cures at 250 or 350 degrees f; for service temperatures 350 degrees f; must be shipped and stored at 0 degrees f or below Material: Plastic epoxy Supplementary Features: 50 square foot Shelf Life: N/a Unit Of Measure: Demilitarization: No	Quantity Within Each Unit Package:
For core splicing applications Features Provided: Heat vulcanize feature Special Features: 12 x 24 in. Sheet; 0.045 to 0.055 in. Thickness; foaming type; non-asbestos; cures at 250 or 350 degrees f; for service temperatures 350 degrees f; must be shipped and stored at 0 degrees f or below Material: Plastic epoxy Supplementary Features: 50 square foot Shelf Life: N/a Unit Of Measure: Demilitarization: No	0.000 square feet
Features Provided: Heat vulcanize feature Special Features: 12 x 24 in. Sheet; 0.045 to 0.055 in. Thickness; foaming type; non-asbestos; cures at 250 or 350 degrees f; for service temperatures 350 degrees f; must be shipped and stored at 0 degrees f or below Material: Plastic epoxy Supplementary Features: 50 square foot Shelf Life: N/a Unit Of Measure: Demilitarization: No	Specific Usage Design:
Heat vulcanize feature Special Features: 12 x 24 in. Sheet; 0.045 to 0.055 in. Thickness; foaming type; non-asbestos; cures at 250 or 350 degrees f; for service temperatures 350 degrees f; must be shipped and stored at 0 degrees f or below Material: Plastic epoxy Supplementary Features: 50 square foot Shelf Life: N/a Unit Of Measure: Demilitarization: No	or core splicing applications
Special Features: 12 x 24 in. Sheet; 0.045 to 0.055 in. Thickness; foaming type; non-asbestos; cures at 250 or 350 degrees f; for service temperatures 350 degrees f; must be shipped and stored at 0 degrees f or below Material: Plastic epoxy Supplementary Features: 50 square foot Shelf Life: N/a Unit Of Measure: Demilitarization: No	eatures Provided:
12 x 24 in. Sheet; 0.045 to 0.055 in. Thickness; foaming type; non-asbestos; cures at 250 or 350 degrees f; for service temperatures 350 degrees f; must be shipped and stored at 0 degrees f or below Material: Plastic epoxy Supplementary Features: 50 square foot Shelf Life: N/a Unit Of Measure: Demilitarization: No	leat vulcanize feature
350 degrees f; must be shipped and stored at 0 degrees f or below Material: Plastic epoxy Supplementary Features: 50 square foot Shelf Life: N/a Unit Of Measure: Demilitarization: No	Special Features:
Material: Plastic epoxy Supplementary Features: 50 square foot Shelf Life: N/a Unit Of Measure: Demilitarization: No	2 x 24 in. Sheet; 0.045 to 0.055 in. Thickness; foaming type; non-asbestos; cures at 250 or 350 degrees f; for service temperatures up to
Plastic epoxy Supplementary Features: 50 square foot Shelf Life: N/a Unit Of Measure: Demilitarization: No	50 degrees f; must be shipped and stored at 0 degrees f or below
Supplementary Features: 50 square foot Shelf Life: N/a Unit Of Measure: Demilitarization: No	flaterial:
50 square foot Shelf Life: N/a Unit Of Measure: Demilitarization: No	Plastic epoxy
Shelf Life: N/a Unit Of Measure: Demilitarization: No	Supplementary Features:
N/a Unit Of Measure: Demilitarization: No	0 square foot
Unit Of Measure: Demilitarization: No	Shelf Life:
Demilitarization: No	I/a
Demilitarization: No	Init Of Measure:
No	
	Demilitarization:
Fiig:	lo
	iig:
A535p0	.535p0