NSN 8040-01-500-8146

Adhesive - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/8040-01-500-8146

| Paste Quantity Within Each Unit Package: 2.000 grams Specific Usage Design: For critical electronic, aerospace and industrial bonding, laminating and reinforcing applications requiring high fill, non-sag characteristic provided: Separate catalyst Rated Drying Time: 24.000 hours Special Features: Thixotropic; low outgassing; service temperature range of minus 60 degrees c to plus 130 degrees c Color: Clear Material: | ıracteristic |
|--|--------------|
| 2.000 grams Specific Usage Design: For critical electronic, aerospace and industrial bonding, laminating and reinforcing applications requiring high fill, non-sag characteristic Features Provided: Separate catalyst Rated Drying Time: 24.000 hours Special Features: Thixotropic; low outgassing; service temperature range of minus 60 degrees c to plus 130 degrees c Color: Clear Material: | ıracteristic |
| Specific Usage Design: For critical electronic, aerospace and industrial bonding, laminating and reinforcing applications requiring high fill, non-sag characteristic features Provided: Separate catalyst Rated Drying Time: 24.000 hours Special Features: Thixotropic; low outgassing; service temperature range of minus 60 degrees c to plus 130 degrees c Color: Clear Material: | ıracteristic |
| For critical electronic, aerospace and industrial bonding, laminating and reinforcing applications requiring high fill, non-sag characteristics. Separate catalyst Rated Drying Time: 24.000 hours Special Features: Thixotropic; low outgassing; service temperature range of minus 60 degrees c to plus 130 degrees c Color: Clear Material: | ıracteristic |
| Features Provided: Separate catalyst Rated Drying Time: 24.000 hours Special Features: Thixotropic; low outgassing; service temperature range of minus 60 degrees c to plus 130 degrees c Color: Clear Material: | ıracteristic |
| Separate catalyst Rated Drying Time: 24.000 hours Special Features: Thixotropic; low outgassing; service temperature range of minus 60 degrees c to plus 130 degrees c Color: Clear Material: | |
| Rated Drying Time: 24.000 hours Special Features: Thixotropic; low outgassing; service temperature range of minus 60 degrees c to plus 130 degrees c Color: Clear Material: | |
| 24.000 hours Special Features: Thixotropic; low outgassing; service temperature range of minus 60 degrees c to plus 130 degrees c Color: Clear Material: | |
| Special Features: Thixotropic; low outgassing; service temperature range of minus 60 degrees c to plus 130 degrees c Color: Clear Material: | |
| Thixotropic; low outgassing; service temperature range of minus 60 degrees c to plus 130 degrees c Color: Clear Material: | |
| Color: Clear Material: | |
| Clear Material: | |
| Material: | |
| | |
| | |
| Plastic epoxy | |
| Supplementary Features: | |
| 2 gram kit | |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |
| | |
| Demilitarization: | |
| No | |
| Fiig: | |
| A535p0 | |