

View Online at <https://aerobasegroup.com/nsn/8040-01-579-3651>

**Tempurature Rating:**

65.0 degrees fahrenheit

**End Application:**

Aircraft applications

**Physical Form:**

Paste

**Quantity Within Each Unit Package:**

1.000 ounces

**Specific Usage Design:**

Shield expansion

**Curing Method:**

Air dried

**Minimum Flash Point:**

51.0 degrees fahrenheit

**Features Provided:**

Separate catalyst

**Rated Drying Time:**

Between 4.000 minutes and 6.000 minutes

**Product Name:**

High strength all purpose adhesive

**Special Features:**

Plexus ma300 is a 2 part methacrylate adhesive designed for structural bonding of metals, themoplastic, composites; contains methacrylic acid; meth methacrylate monomer; chlorosulfonated polyethylene; carbon tetrachloride; hmis fire hazard 3; hmis health hazard 2; hmis reactivi type 2

**Color:**

Off-white

**Material:**

Plastic methyl methacrylate

**Supplementary Features:**

Dot shipping name adhesives; dot un no.1133; dot hazard class 3; dot packing group ii; dot exemption-orm-d small quantity exemption; flammable

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A535p0