## NSN 8120-00-074-4949

Gas Cylinder Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/8120-00-074-4949

view Online at https://aerobasegroup.com/nsn/8120-00-074-4949
Body Material:
Brass, qq-b-626, comp 21
Maximum Operating Pressure:
2200.0 pounds per square inch
Outside Surface Treatment:
Chromium
Body Style:
Angle give "adqm" and "adqn" only if flanged one or two ends
Stem Material:
Brass, qq-b-626, comp 11 and bronze, qq-a-630, comp 2 and bronze, qq-m-80 and steel, qq-s-763, class 302, 303, or 304
Furnished Items:
Cap and safety device
Media For Which Designed:
Nitrous oxygen
First End Connection Type:
Threaded external gas cylinder
First End Style Designator:
Plain
First End Thread Direction:
Right-hand
Second End Relationship With First End:
Not identical
Second End Connection Type:
Threaded external gas cylinder
Second End Style Designator:
Plain
Second End Thread Direction:
Right-hand
Seat Material:
Brass, qq-b-626, comp 21
Flow Control Device:
Disk, flat
Flow Control Device Material:
Cloth, nylon or plastic, mil-p-15047
Valve Operation Method:
Wheel
End Connection Quantity:
2
First End Thread Pitch Diameters

Product Name:

+0.7750 to 0.7786 inches

Valve cylinder gas nitrous oxide 3/4 inch

## NSN 8120-00-074-4949

Gas Cylinder Valve - Page 2 of 2



Special	Features:
---------	-----------

0.75-IN-.(1-.9CM

**Special Markings:** 

Nitrous-oxide med

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A07100