## NSN 8120-00-142-9241

Gas Cylinder Valve - Page 1 of 2




View Online at https://aerobasegroup.com/nsn/8120-00-142-9241

## **Body Material:** Any acceptable Maximum Operating Pressure: 600.0 pounds per square inch **Body Style:** Angle give "adqm" and "adqn" only if flanged one or two ends **Stem Material:** Any acceptable **Tempurature Rating:** 67.0 degrees fahrenheit Media For Which Designed: Butane or propane gas or butane-propane mixtures or mapp gas First End Connection Type: Threaded internal gas cylinder First End Style Designator: Gasket seal **First End Thread Direction:** Left-hand Second End Relationship With First End: Not identical Second End Connection Type: Threaded external gas cylinder Second End Style Designator: Plain Second End Thread Direction: **Right-hand Flow Control Device:** Any acceptable **Flow Control Device Material:** Any acceptable Valve Operation Method: Wheel **End Connection Quantity:** 2 **First End Thread Pitch Diameters:** +0.8386/+0.8422 inches Second End Thread Pitch Diameters: +0.9677/+1.0157 inches **Special Features:** USED-WI-THC-YLIN **Special Markings:**

Lpg

## NSN 8120-00-142-9241

Gas Cylinder Valve - Page 2 of 2



V14-510 type

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A07100

