NSN 8120-00-886-2301

Gas Cylinder Valve - Page 1 of 2

Body Material:

Brass, qq-b-626, comp 21



View Online at https://aerobasegroup.com/nsn/8120-00-886-2301

Maximum Operating Pressure:
2265.0 pounds per square inch
Body Style:
Angle give "adqm" and "adqn" only if flanged one or two ends
Stem Material:
Any acceptable
Furnished Items:
Chain and plug
Tempurature Rating:
70.0 degrees fahrenheit
Media For Which Designed:
Sulphur hexafluoride
First End Connection Type:
Threaded internal gas cylinder
First End Style Designator:
Flare
First End Thread Direction:
Left-hand
Second End Relationship With First End:
Not identical
Second End Connection Type:
Threaded external gas cylinder
Second End Style Designator:
Plain beveled
Second End Thread Direction:
Right-hand
Seat Material:
Any acceptable
Flow Control Device:
Any acceptable
Flow Control Device Material:
Any acceptable
Valve Operation Method:
Wheel
End Connection Quantity:
2
First End Thread Pitch Diameters:
+0.9186/+0.9222 inches
Second End Thread Pitch Diameters:
+0.9677/+1.0157 inches

NSN 8120-00-886-2301

Gas Cylinder Valve - Page 2 of 2



	cia			

Sulphur hexafluoride med

Specification Or Standard:

V46-591-2 type

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A07100