NSN 8120-00-886-2301

Gas Cylinder Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/8120-00-886-2301

Body Material:

Brass, qq-b-626, comp 21

Maximum Operating Pressure:

2265.0 pounds per square inch

Body Style:

Angle give "adqm" and "adqn" only if flanged one or two ends

Stem Material:

Any acceptable

Furnished Items:

Chain and plug

Tempurature Rating:

70.0 degrees fahrenheit

Media For Which Designed:

Sulphur hexafluoride

First End Connection Type:

Threaded internal gas cylinder

First End Style Designator:

Flare

First End Thread Direction:

Left-hand

Second End Relationship With First End:

Not identical

Second End Connection Type:

Threaded external gas cylinder

Second End Style Designator:

Plain beveled

Second End Thread Direction:

Right-hand

Seat Material:

Any acceptable

Flow Control Device:

Any acceptable

Flow Control Device Material:

Any acceptable

Valve Operation Method:

Wheel

End Connection Quantity:

2

First End Thread Pitch Diameters:

+0.9186/+0.9222 inches

Second End Thread Pitch Diameters:

+0.9677/+1.0157 inches

NSN 8120-00-886-2301

Gas Cylinder Valve - Page 2 of 2

Special Markings:

Sulphur hexafluoride med

Specification Or Standard:

V46-591-2 type

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A07100

