

View Online at <https://aerobasegroup.com/nsn/8120-01-156-0716>

Special Features:

316l and or 304l stainless steel; one ton cap; 1682 pounds non water cap; 81.5 in. O/a lg; 30 in. Od; nom metal thk 0.406 in. Min wall; 0.75 in. Min ends; tank meets icc reg rel to shpt oftoxic gas; 500 psi maximum wk pressure; 2 eduction tubes 0.5 in. Id; valve hole thd 0.75 in. Non ips 14 ths per in.Npt specification 0.75 in. Depth thd; valve for nitrogen tetroxide; supperior valve company washington pa dwg 5983x90, valve meets icc reg for shipping toxic gas; w/gasketed, bolted gas tight valve; protective shipping bonnett.

General Description:

4316l and or 304l stainless steel; one ton cap; 1682 pounds non water cap; 81.5 in. O/a lg; 30 in. Od; nom metal thk 0.406 in. Min wall; 0.75 in. Min ends; tank meets icc reg rel to shpt oftoxic gas; 500 psi maximum wk pressure; 2 eduction tubes 0.5 in. Id; valve hole thd 0.75 in. Non ips 14 ths per in.Npt specification 0.75 in. Depth thd; valve for nitrogen tetroxide; supperior valve company washington pa dwg 5983x90, valve meets icc reg for shipping toxic gas; w/gasketed, bolted gas tight valve; protective shipping bonnett

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A23900