NSN 8120-01-325-6128

Gas Cylinder Valve - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/8120-01-325-6128 |
|---|
| Body Material: |
| Brass, qq-b-626, comp 21 |
| Maximum Operating Pressure: |
| 2265.0 pounds per square inch |
| Body Style: |
| Angle give "adqm" and "adqn" only if flanged one or two ends |
| Stem Material: |
| Any acceptable |
| Furnished Items: |
| Safety device |
| Tempurature Rating: |
| 70.0 degrees fahrenheit |
| Media For Which Designed: |
| Hexafluoroethane |
| First End Connection Type: |
| Threaded external gas cylinder |
| First End Style Designator: |
| Flareless |
| First End Thread Class: |
| 1a |
| First End Thread Direction: |
| Right-hand |
| Second End Relationship With First End: |
| Not identical |
| Second End Connection Type: |
| Threaded external gas cylinder |
| Second End Style Designator: |
| Flareless |
| Second End Thread Class: |
| 1b |
| Second End Thread Direction: |
| Right-hand |
| Seat Material: |
| Brass, qq-b-626, comp 21 |
| First Connection Face To Centerline Distance: |
| 1.625 inches |

Second Connection Face To Centerline Distance:

1.781 inches

Flow Control Device:

Any acceptable

Flow Control Device Material:

Any acceptable

NSN 8120-01-325-6128

Gas Cylinder Valve - Page 2 of 2



| Valve Operation Method: |
|--------------------------------------|
| Wheel |
| End Connection Quantity: |
| 2 |
| First End Thread Pitch Diameters: |
| +0.9796/+0.9836 inches |
| Second End Thread Pitch Diameters: |
| +0.9677/+1.0157 inches |
| First End Thread Series Designator: |
| Ngo |
| Second End Thread Series Designator: |
| Ngt |
| Special Features: |
| DIAP-HR-AGM-PACK |
| Special Markings: |
| Refrigerant |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A07100 |