NSN 8120-01-325-6128

Gas Cylinder Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/8120-01-325-6128

Body Material:

Brass, qq-b-626, comp 21

Maximum Operating Pressure:

2265.0 pounds per square inch

Body Style:

Angle give "adqm" and "adqn" only if flanged one or two ends

Stem Material:

Any acceptable

Furnished Items:

Safety device

Tempurature Rating:

70.0 degrees fahrenheit

Media For Which Designed:

Hexafluoroethane

First End Connection Type:

Threaded external gas cylinder

First End Style Designator:

Flareless

First End Thread Class:

1a

First End Thread Direction:

Right-hand

Second End Relationship With First End:

Not identical

Second End Connection Type:

Threaded external gas cylinder

Second End Style Designator:

Flareless

Second End Thread Class:

1b

Second End Thread Direction:

Right-hand

Seat Material:

Brass, qq-b-626, comp 21

First Connection Face To Centerline Distance:

1.625 inches

Second Connection Face To Centerline Distance:

1.781 inches

Flow Control Device:

Any acceptable

Flow Control Device Material:

Any acceptable

NSN 8120-01-325-6128 Gas Cylinder Valve - Page 2 of 2

| Aero | Base |
|------|-------|
| | Group |

| Valve Operation Method: |
|--------------------------------------|
| Wheel |
| End Connection Quantity: |
| 2 |
| First End Thread Pitch Diameters: |
| +0.9796/+0.9836 inches |
| Second End Thread Pitch Diameters: |
| +0.9677/+1.0157 inches |
| First End Thread Series Designator: |
| Ngo |
| Second End Thread Series Designator: |
| Ngt |
| Special Features: |
| DIAP-HR-AGM-PACK |
| Special Markings: |
| Refrigerant |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A07100 |
| |