NSN 8140-01-527-2148

Shipping And Storage Container Wear Plate - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/8140-01-527-2148

Overall Height: 19.820 inches Overall Width: 20.100 inches Eind Application: Wik 14 mod 2, cannister Product Name: Protective plate Special Features: R0.075 in. Thick; rectangular; with long side down, has cutouts on each top corner: 0.65 in. W x 0.75 in. D, and larger cutouts at same corners: 4.80 in. W x 3.070 in. Deep: top edge rolls back with radius of 0.18 in. For length of 0.25 in.; has 6 mounting holes, 0.375 inch in lia: 2 near top edge: 7.547 and 12.453 in. From left outside edge and 18.280 inch from bottom edge and 4 holes 0.750 inch from bottom edge and 3.448, 7.848, 12.248 and 16.848 inches from left edge Special Markings: 33711-7251124-1 iaw mil-std-130 in characters approx. 0.19 in. Surface Treatment: Paint side from which top rolls back per ws19201, gr f and other side coat per ws20168, overspray onto edges and holes is permitted supplementary Features: Has rectangular cutout: 4.00 in. W x 2.00 in. H, beginning 9.50 in. From left edge and 1.63 in. From bottom edge; has 5 more holes, 0.500 noch in dia: 1 near top edge: 18.280 in. From bottom and 6.255 in from left edge 4 holes near bottom edge: 2.880 in. From bottom and 8.895, 3.775, 4.775, and 7.545 in. From left edge Obtitl Of Measure: Ditti Of Measure: Ditti Of Measure: Ditti Of Measure: Demilitarization:
Powerall Width: 20.100 inches End Application: Wik 14 mod 2, cannister Product Name: Protective plate Special Features: 80.075 in. Thick; rectangular; with long side down, has cutouts on each top corner: 0.65 in. W x 0.75 in. D, and larger cutouts at same corners: 4.80 in. W x 3.070 in. Deep: top edge rolls back with radius of 0.18 in. For length of 0.25 in.; has 6 mounting holes, 0.375 inch in dia: 2 near top edge: 7.547 and 12.453 in. From left outside edge and 18.280 inch from bottom edge and 4 holes 0.750 inch from bottom edge and 3.448, 7.848, 12.248 and 16.848 inches from left edge Special Markings: 63711-7251124-1 iaw mil-std-130 in characters approx. 0.19 in. Surface Treatment: Paint side from which top rolls back per ws19201, gr f and other side coat per ws20168, overspray onto edges and holes is permitted Supplementary Features: Has rectangular cutout: 4.00 in. W x 2.00 in. H, beginning 9.50 in. From left edge and 1.63 in. From bottom edge; has 5 more holes, 0.500 inch in dia: 1 near top edge: 18.280 in. From bottom and 6.255 in from left edge 4 holes near bottom edge: 2.880 in. From bottom and 2.895, 3.775, 4.775, and 7.545 in. From left edge Shelf Life: Wa Juit Of Measure: Demilitarization: No
20.100 inches End Application: Alk 14 mod 2, cannister Product Name: Protective plate Special Features: 80.075 in. Thick; rectangular; with long side down, has cutouts on each top corner: 0.65 in. W x 0.75 in. D, and larger cutouts at same corners: 4.80 in. W x 3.070 in. Deep: top edge rolls back with radius of 0.18 in. For length of 0.25 in.; has 6 mounting holes, 0.375 inch in dia: 2 near top edge: 7.547 and 12.453 in. From left outside edge and 18.280 inch from bottom edge and 4 holes 0.750 inch from bottom edge and 3.448, 7.848, 12.248 and 16.848 inches from left edge Special Markings: Special Markings: Special Markings: Paint side from which top rolls back per ws19201, gr f and other side coat per ws20168, overspray onto edges and holes is permitted Supplementary Features: Has rectangular cutout: 4.00 in. W x 2.00 in. H, beginning 9.50 in. From left edge and 1.63 in. From bottom edge; has 5 more holes, 0.500 nch in dia: 1 near top edge: 18.280 in. From bottom and 6.255 in from left edge 4 holes near bottom edge: 2.880 in. From bottom and 6.895, 3.775, 4.775, and 7.545 in. From left edge Shelf Life: Via Unit Of Measure: Domilitarization:
End Application: Wk 14 mod 2, cannister Product Name: Protective plate Special Features: R0.075 in. Thick; rectangular; with long side down, has cutouts on each top corner: 0.65 in. W x 0.75 in. D, and larger cutouts at same corners: 4.80 in. W x 3.070 in. Deep: top edge rolls back with radius of 0.18 in. For length of 0.25 in.; has 6 mounting holes, 0.375 inch in dia: 2 near top edge: 7.547 and 12.453 in. From left outside edge and 18.280 inch from bottom edge and 4 holes 0.750 inch from bottom edge and 3.448, 7.848, 12.248 and 16.848 inches from left edge Special Markings: Surface Treatment: Paint side from which top rolls back per ws19201, gr f and other side coat per ws20168, overspray onto edges and holes is permitted Supplementary Features: Has rectangular cutout: 4.00 in. W x 2.00 in. H, beginning 9.50 in. From left edge and 1.63 in. From bottom edge; has 5 more holes, 0.500 nch in dia: 1 near top edge: 18.280 in. From bottom and 2.895, 3.775, 4.775, and 7.545 in. From left edge Shelf Life: Wa Unit Of Measure: Domilitarization:
Orbital Special Features: Rough Special Markings: Rough Markings: Rough Markings: Rough Special Markings: Rough Spec
Product Name: Protective plate Special Features: R0.075 in. Thick; rectangular; with long side down, has cutouts on each top corner: 0.65 in. W x 0.75 in. D, and larger cutouts at same corners: 4.80 in. W x 3.070 in. Deep: top edge rolls back with radius of 0.18 in. For length of 0.25 in.; has 6 mounting holes, 0.375 inch in dia: 2 near top edge: 7.547 and 12.453 in. From left outside edge and 18.280 inch from bottom edge and 4 holes 0.750 inch from bottom edge and 3.448, 7.848, 12.248 and 16.848 inches from left edge Special Markings: 63711-7251124-1 iaw mil-std-130 in characters approx. 0.19 in. Surface Treatment: Paint side from which top rolls back per ws19201, gr f and other side coat per ws20168, overspray onto edges and holes is permitted Supplementary Features: Has rectangular cutout: 4.00 in. W x 2.00 in. H, beginning 9.50 in. From left edge and 1.63 in. From bottom edge; has 5 more holes, 0.500 inch in dia: 1 near top edge: 18.280 in. From bottom and 6.255 in from left edge 4 holes near bottom edge: 2.880 in. From bottom and 2.895, 3.775, 4.775, and 7.545 in. From left edge Shelf Life: Wa Juit Of Measure: - Demilitarization: No
Protective plate Special Features: 80.075 in. Thick; rectangular; with long side down, has cutouts on each top corner: 0.65 in. W x 0.75 in. D, and larger cutouts at same corners: 4.80 in. W x 3.070 in. Deep: top edge rolls back with radius of 0.18 in. For length of 0.25 in.; has 6 mounting holes, 0.375 inch in dia: 2 near top edge: 7.547 and 12.453 in. From left outside edge and 18.280 inch from bottom edge and 4 holes 0.750 inch from bottom edge and 3.448, 7.848, 12.248 and 16.848 inches from left edge Special Markings: 33711-7251124-1 iaw mil-std-130 in characters approx. 0.19 in. Surface Treatment: Paint side from which top rolls back per ws19201, gr f and other side coat per ws20168, overspray onto edges and holes is permitted supplementary Features: Has rectangular cutout: 4.00 in. W x 2.00 in. H, beginning 9.50 in. From left edge and 1.63 in. From bottom edge; has 5 more holes, 0.500 inch in dia: 1 near top edge: 18.280 in. From bottom and 6.255 in from left edge 4 holes near bottom edge: 2.880 in. From bottom and 2.895, 3.775, 4.775, and 7.545 in. From left edge Shelf Life: Wa Unit Of Measure: Demilitarization:
Special Features: R0.075 in. Thick; rectangular; with long side down, has cutouts on each top corner: 0.65 in. W x 0.75 in. D, and larger cutouts at same corners: 4.80 in. W x 3.070 in. Deep: top edge rolls back with radius of 0.18 in. For length of 0.25 in.; has 6 mounting holes, 0.375 inch in dia: 2 near top edge: 7.547 and 12.453 in. From left outside edge and 18.280 inch from bottom edge and 4 holes 0.750 inch from bottom edge and 3.448, 7.848, 12.248 and 16.848 inches from left edge Special Markings: 33711-7251124-1 iaw mil-std-130 in characters approx. 0.19 in. Surface Treatment: Paint side from which top rolls back per ws19201, gr f and other side coat per ws20168, overspray onto edges and holes is permitted supplementary Features: Has rectangular cutout: 4.00 in. W x 2.00 in. H, beginning 9.50 in. From left edge and 1.63 in. From bottom edge; has 5 more holes, 0.500 inch in dia: 1 near top edge: 18.280 in. From bottom and 6.255 in from left edge 4 holes near bottom edge: 2.880 in. From bottom and 2.895, 3.775, 4.775, and 7.545 in. From left edge Shelf Life: Wa Unit Of Measure: Demilitarization:
R0.075 in. Thick; rectangular; with long side down, has cutouts on each top corner: 0.65 in. W x 0.75 in. D, and larger cutouts at same corners: 4.80 in. W x 3.070 in. Deep: top edge rolls back with radius of 0.18 in. For length of 0.25 in.; has 6 mounting holes, 0.375 inch in dia: 2 near top edge: 7.547 and 12.453 in. From left outside edge and 18.280 inch from bottom edge and 4 holes 0.750 inch from bottom edge and 3.448, 7.848, 12.248 and 16.848 inches from left edge special Markings: 83711-7251124-1 iaw mil-std-130 in characters approx. 0.19 in. 83711-7251124-1 iaw mil-std-130 in. From bottom approx. 0.19 in. 83711-7251124-
corners: 4.80 in. W x 3.070 in. Deep: top edge rolls back with radius of 0.18 in. For length of 0.25 in.; has 6 mounting holes, 0.375 inch in dia: 2 near top edge: 7.547 and 12.453 in. From left outside edge and 18.280 inch from bottom edge and 4 holes 0.750 inch from bottom edge and 3.448, 7.848, 12.248 and 16.848 inches from left edge Special Markings: 63711-7251124-1 iaw mil-std-130 in characters approx. 0.19 in. Surface Treatment: Paint side from which top rolls back per ws19201, gr f and other side coat per ws20168, overspray onto edges and holes is permitted Supplementary Features: Has rectangular cutout: 4.00 in. W x 2.00 in. H, beginning 9.50 in. From left edge and 1.63 in. From bottom edge; has 5 more holes, 0.500 inch in dia: 1 near top edge: 18.280 in. From bottom and 6.255 in from left edge 4 holes near bottom edge: 2.880 in. From bottom and 6.895, 3.775, 4.775, and 7.545 in. From left edge Shelf Life: No Juit Of Measure: Demilitarization:
dia: 2 near top edge: 7.547 and 12.453 in. From left outside edge and 18.280 inch from bottom edge and 4 holes 0.750 inch from bottom edge and 3.448, 7.848, 12.248 and 16.848 inches from left edge special Markings: 63711-7251124-1 iaw mill-std-130 in characters approx. 0.19 in. 634711-7251124-1 iaw mill-std-130 in characters approx. 0.19 in. 64584 64684 65494 65494 65494 65494 65495 65496
Special Markings: 63711-7251124-1 iaw mil-std-130 in characters approx. 0.19 in. 63711-7251124-1 iaw mil-std-130 in. characters approx. 0.19 in. 6371
Special Markings: 63711-7251124-1 iaw mil-std-130 in characters approx. 0.19 in. Surface Treatment: Paint side from which top rolls back per ws19201, gr f and other side coat per ws20168, overspray onto edges and holes is permitted Supplementary Features: Has rectangular cutout: 4.00 in. W x 2.00 in. H, beginning 9.50 in. From left edge and 1.63 in. From bottom edge; has 5 more holes, 0.500 inch in dia: 1 near top edge: 18.280 in. From bottom and 6.255 in from left edge 4 holes near bottom edge: 2.880 in. From bottom and 6.895, 3.775, 4.775, and 7.545 in. From left edge Shelf Life: N/a Unit Of Measure: - Demilitarization:
Surface Treatment: Paint side from which top rolls back per ws19201, gr f and other side coat per ws20168, overspray onto edges and holes is permitted Supplementary Features: Has rectangular cutout: 4.00 in. W x 2.00 in. H, beginning 9.50 in. From left edge and 1.63 in. From bottom edge; has 5 more holes, 0.500 in. hi dia: 1 near top edge: 18.280 in. From bottom and 6.255 in from left edge 4 holes near bottom edge: 2.880 in. From bottom and 2.895, 3.775, 4.775, and 7.545 in. From left edge Shelf Life: N/a Unit Of Measure: - Demilitarization: No
Surface Treatment: Paint side from which top rolls back per ws19201, gr f and other side coat per ws20168, overspray onto edges and holes is permitted Supplementary Features: Has rectangular cutout: 4.00 in. W x 2.00 in. H, beginning 9.50 in. From left edge and 1.63 in. From bottom edge; has 5 more holes, 0.500 inch in dia: 1 near top edge: 18.280 in. From bottom and 6.255 in from left edge 4 holes near bottom edge: 2.880 in. From bottom and 2.895, 3.775, 4.775, and 7.545 in. From left edge Shelf Life: N/a Unit Of Measure: - Demilitarization: No
Paint side from which top rolls back per ws19201, gr f and other side coat per ws20168, overspray onto edges and holes is permitted Supplementary Features: Has rectangular cutout: 4.00 in. W x 2.00 in. H, beginning 9.50 in. From left edge and 1.63 in. From bottom edge; has 5 more holes, 0.500 inch in dia: 1 near top edge: 18.280 in. From bottom and 6.255 in from left edge 4 holes near bottom edge: 2.880 in. From bottom and 2.895, 3.775, 4.775, and 7.545 in. From left edge Shelf Life: N/a Unit Of Measure: Demilitarization: No
Supplementary Features: Has rectangular cutout: 4.00 in. W x 2.00 in. H, beginning 9.50 in. From left edge and 1.63 in. From bottom edge; has 5 more holes, 0.500 inch in dia: 1 near top edge: 18.280 in. From bottom and 6.255 in from left edge 4 holes near bottom edge: 2.880 in. From bottom and 2.895, 3.775, 4.775, and 7.545 in. From left edge Shelf Life: No Demilitarization: No
Has rectangular cutout: 4.00 in. W x 2.00 in. H, beginning 9.50 in. From left edge and 1.63 in. From bottom edge; has 5 more holes, 0.500 nch in dia: 1 near top edge: 18.280 in. From bottom and 6.255 in from left edge 4 holes near bottom edge: 2.880 in. From bottom and 2.895, 3.775, 4.775, and 7.545 in. From left edge Shelf Life: N/a Jnit Of Measure: Demilitarization: No
nch in dia: 1 near top edge: 18.280 in. From bottom and 6.255 in from left edge 4 holes near bottom edge: 2.880 in. From bottom and 2.895, 3.775, 4.775, and 7.545 in. From left edge Shelf Life: N/a Unit Of Measure: Demilitarization: No
2.895, 3.775, 4.775, and 7.545 in. From left edge Shelf Life: N/a Jnit Of Measure: Demilitarization:
Shelf Life: N/a Unit Of Measure: - Demilitarization:
N/a Jnit Of Measure: - Demilitarization:
Jnit Of Measure: - Demilitarization:
- Demilitarization:
No
No
Filg:
A23900