## NSN 8140-01-527-2153

Shipping And Storage Container Wear Plate - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/8140-01-527-2153

Overall Height:  19.820 inches  Overall Width:  20.100 inches  End Application:  Mk 14 mod 2, cannister  Product Name:  Protective plate  Special Features:  W0.075 in. Thick; rectangular; with long side down, has cutouts on each top corner: 0.65 in. W x 0.75 in. D, and larger cutouts corners: 4.80 in. W x 3.070 in. Deep: top edge rolls back with radius of 0.18 in. For length of 0.25 in.; has 6 mounting holes, 0.3 dia.: 2 near top edge: 7.547 and 12.453 in. From left outside edge and 18.280 inch from bottom edge and 4 near bottom edge: 6 from bottom edge and 3.448, 7.848, 12.248 and 16.848 inches from left edge  Special Markings:  53711-7251124-1 iaw mil-std-130 in characters approx. 0.19 in.  Surface Treatment:  Paint side from which top rolls back per ws19201, gr f and other side coat per ws20168, overspray onto edges and holes is perm	
Overall Width:  20.100 inches  End Application:  Mk 14 mod 2, cannister  Product Name:  Protective plate  Special Features:  W0.075 in. Thick; rectangular; with long side down, has cutouts on each top corner: 0.65 in. W x 0.75 in. D, and larger cutouts corners: 4.80 in. W x 3.070 in. Deep: top edge rolls back with radius of 0.18 in. For length of 0.25 in.; has 6 mounting holes, 0.3 dia.: 2 near top edge: 7.547 and 12.453 in. From left outside edge and 18.280 inch from bottom edge and 4 near bottom edge: from bottom edge and 3.448, 7.848, 12.248 and 16.848 inches from left edge  Special Markings:  53711-7251124-1 iaw mil-std-130 in characters approx. 0.19 in.  Surface Treatment:	
20.100 inches  End Application:  Mk 14 mod 2, cannister  Product Name:  Protective plate  Special Features:  W0.075 in. Thick; rectangular; with long side down, has cutouts on each top corner: 0.65 in. W x 0.75 in. D, and larger cutouts corners: 4.80 in. W x 3.070 in. Deep: top edge rolls back with radius of 0.18 in. For length of 0.25 in.; has 6 mounting holes, 0.3 dia.: 2 near top edge: 7.547 and 12.453 in. From left outside edge and 18.280 inch from bottom edge and 4 near bottom edge: from bottom edge and 3.448, 7.848, 12.248 and 16.848 inches from left edge  Special Markings:  53711-7251124-1 iaw mil-std-130 in characters approx. 0.19 in.  Surface Treatment:	
End Application:  Mk 14 mod 2, cannister  Product Name:  Protective plate  Special Features:  W0.075 in. Thick; rectangular; with long side down, has cutouts on each top corner: 0.65 in. W x 0.75 in. D, and larger cutouts corners: 4.80 in. W x 3.070 in. Deep: top edge rolls back with radius of 0.18 in. For length of 0.25 in.; has 6 mounting holes, 0.3 dia.: 2 near top edge: 7.547 and 12.453 in. From left outside edge and 18.280 inch from bottom edge and 4 near bottom edge: from bottom edge and 3.448, 7.848, 12.248 and 16.848 inches from left edge  Special Markings:  53711-7251124-1 iaw mil-std-130 in characters approx. 0.19 in.  Surface Treatment:	
Mk 14 mod 2, cannister  Product Name:  Protective plate  Special Features:  W0.075 in. Thick; rectangular; with long side down, has cutouts on each top corner: 0.65 in. W x 0.75 in. D, and larger cutouts corners: 4.80 in. W x 3.070 in. Deep: top edge rolls back with radius of 0.18 in. For length of 0.25 in.; has 6 mounting holes, 0.3 dia.: 2 near top edge: 7.547 and 12.453 in. From left outside edge and 18.280 inch from bottom edge and 4 near bottom edge: from bottom edge and 3.448, 7.848, 12.248 and 16.848 inches from left edge  Special Markings:  53711-7251124-1 iaw mil-std-130 in characters approx. 0.19 in.  Surface Treatment:	
Product Name: Protective plate  Special Features:  W0.075 in. Thick; rectangular; with long side down, has cutouts on each top corner: 0.65 in. W x 0.75 in. D, and larger cutouts corners: 4.80 in. W x 3.070 in. Deep: top edge rolls back with radius of 0.18 in. For length of 0.25 in.; has 6 mounting holes, 0.3 dia.: 2 near top edge: 7.547 and 12.453 in. From left outside edge and 18.280 inch from bottom edge and 4 near bottom edge: from bottom edge and 3.448, 7.848, 12.248 and 16.848 inches from left edge  Special Markings:  53711-7251124-1 iaw mil-std-130 in characters approx. 0.19 in.  Surface Treatment:	
Protective plate  Special Features:  W0.075 in. Thick; rectangular; with long side down, has cutouts on each top corner: 0.65 in. W x 0.75 in. D, and larger cutouts corners: 4.80 in. W x 3.070 in. Deep: top edge rolls back with radius of 0.18 in. For length of 0.25 in.; has 6 mounting holes, 0.3 dia.: 2 near top edge: 7.547 and 12.453 in. From left outside edge and 18.280 inch from bottom edge and 4 near bottom edge: from bottom edge and 3.448, 7.848, 12.248 and 16.848 inches from left edge  Special Markings:  53711-7251124-1 iaw mil-std-130 in characters approx. 0.19 in.  Surface Treatment:	
Special Features:  W0.075 in. Thick; rectangular; with long side down, has cutouts on each top corner: 0.65 in. W x 0.75 in. D, and larger cutouts corners: 4.80 in. W x 3.070 in. Deep: top edge rolls back with radius of 0.18 in. For length of 0.25 in.; has 6 mounting holes, 0.3 dia.: 2 near top edge: 7.547 and 12.453 in. From left outside edge and 18.280 inch from bottom edge and 4 near bottom edge: from bottom edge and 3.448, 7.848, 12.248 and 16.848 inches from left edge  Special Markings:  53711-7251124-1 iaw mil-std-130 in characters approx. 0.19 in.  Surface Treatment:	
W0.075 in. Thick; rectangular; with long side down, has cutouts on each top corner: 0.65 in. W x 0.75 in. D, and larger cutouts corners: 4.80 in. W x 3.070 in. Deep: top edge rolls back with radius of 0.18 in. For length of 0.25 in.; has 6 mounting holes, 0.3 dia.: 2 near top edge: 7.547 and 12.453 in. From left outside edge and 18.280 inch from bottom edge and 4 near bottom edge: from bottom edge and 3.448, 7.848, 12.248 and 16.848 inches from left edge  Special Markings: 53711-7251124-1 iaw mil-std-130 in characters approx. 0.19 in.  Surface Treatment:	
corners: 4.80 in. W x 3.070 in. Deep: top edge rolls back with radius of 0.18 in. For length of 0.25 in.; has 6 mounting holes, 0.3 dia.: 2 near top edge: 7.547 and 12.453 in. From left outside edge and 18.280 inch from bottom edge and 4 near bottom edge: 6 from bottom edge and 3.448, 7.848, 12.248 and 16.848 inches from left edge  Special Markings: 53711-7251124-1 iaw mil-std-130 in characters approx. 0.19 in.  Surface Treatment:	
dia.: 2 near top edge: 7.547 and 12.453 in. From left outside edge and 18.280 inch from bottom edge and 4 near bottom edge: 6 from bottom edge and 3.448, 7.848, 12.248 and 16.848 inches from left edge  Special Markings:  53711-7251124-1 iaw mil-std-130 in characters approx. 0.19 in.  Surface Treatment:	at same
from bottom edge and 3.448, 7.848, 12.248 and 16.848 inches from left edge  Special Markings:  53711-7251124-1 iaw mil-std-130 in characters approx. 0.19 in.  Surface Treatment:	75 inch i
Special Markings: 53711-7251124-1 iaw mil-std-130 in characters approx. 0.19 in. Surface Treatment:	).750 incl
53711-7251124-1 iaw mil-std-130 in characters approx. 0.19 in.  Surface Treatment:	
Surface Treatment:	
Paint side from which top rolls back per ws19201, gr f and other side coat per ws20168, overspray onto edges and holes is pern	
	itted
Supplementary Features:	
Ehas 1 more hole, 1.00 inch in dia, 3.500 in. From bottom edge and 12.000 in. From left edge; has 2 additional holes, 0.500 in.	In dia:
2.880 in. From bottom and 10.000 and 16.750 in. From left edge	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A23900	