NSN 8930-01-493-9130

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/8930-01-493-9130

Inside Diameter:

0.250 inches single connection

Overall Length:

8.000 inches

Body Length:

3.000 inches

Overall Diameter:

0.870 inches

End Application:

AIRC-ON-DIT-IONE

Pressure Switch Type:

Gage

Operating Tempurature Rating:

Between -40.0 degrees celsius and 125.0 degrees celsius

Contact Action Stimulus:

Decrease

Proof Pressure:

500.00 pounds per square inch gage

Nonpile-up Contact Arrangement:

1 pole, single throw, normally closed, momentary action

Terminal Type:

Wire lead

Contact Load Current Rating:

5.0 milliamperes resistive load single voltage and 2.0 amperes resistive load single voltage

Contact Adjustability:

Actuation point not adjustable and deactuation point not adjustable

Contact Stimulus Rating:

3.00 actuation point pounds per square inch and 6.00 deactuation point pounds per square inch

Contact Voltage Rating In Volts:

9.0 dc at sea level first voltage

Pressure Connector Type:

Swivel nut, flare, threaded internal single connection

Special Features:

Refrigerant operating temperature -60 degrees c to +135 degrees c; life under miliamp load 1, 000, 000 cycles; resistance to vibration 20 gram from 50 to 200 hz, 8 hours in x-y-z direction

Media For Which Designed:

Gas or liquid

Style Designator:

Cylindrical

Shelf Life:

N/a

Unit Of Measure:

NSN 8930-01-493-9130

Pressure Switch - Page 2 of 2

Demilitarization:

No

Fiig:

A048b0

