

View Online at <https://aerobasegroup.com/nsn/9130-01-207-7763>

**Quantity Within Each Unit Package:**

55.0 gallons

**Maximum Sulphur Content Percentage By Weight:**

0.3

**Freezing Point Maximum Temp:**

-47.0 degrees celsius

**Fuel Grade Classification:**

Jet a-1

**Viscosity At Rated Temp:**

8.00 -20 degrees celsius

**Maximum Aromatics Percentage By Volume:**

20.0

**Distillation Point Percentage At Maximum Temp:**

204.4degcelsiusat10.0percent

**Specific Gravity Value At 15.56 Deg Celsius:**

0.8024

**Copper Corrosion Classification Number:**

1

**Minimum Heat Of Combustion Value:**

18400.0 british thermal units per pound

**Maximum Distillation Loss Volume Percentage:**

1.5

**Minimum Flash Point And Test Method:**

37.8 degrees celsius tag closed cup

**Supply Classification:**

Packaged

**Maximum Amount Of Existent Gum:**

7.0

**Test Data Document:**

81346-astmd1655 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A090a0