

View Online at <https://aerobasegroup.com/nsn/9130-01-208-4172>

**Quantity Within Each Unit Package:**

55.0 gallons

**Maximum Sulphur Content Percentage By Weight:**

0.10

**Reid Vapor Pressure Rating:**

79.0 kilopascals

**Astm Motor Method Minimum Octane Number:**

82.0

**Astm Research Method Minimum Octane Number:**

92.0

**Distillation Point Percentage At Maximum Temp:**

77.0degcelsiusat50.0percent

**Maximum Distillation Residue Volume Percentage:**

2.0

**Copper Corrosion Classification Number:**

1

**Maximum Allowable Tetraethyl Lead:**

0.013 grams per liter

**Supply Classification:**

Packaged

**Maximum Amount Of Existent Gum:**

5.0

**Color:**

Undyed-invalid

**Test Data Document:**

81348-vvg1690 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A090a0