

View Online at <https://aerobasegroup.com/nsn/9130-01-234-1737>

Maximum Sulphur Content Percentage By Weight:

0.3

Freezing Point Maximum Temp:

-50.0 degrees celsius

Fuel Grade Classification:

Kero/b

Reid Vapor Pressure Rating:

Between 14.0 kilopascals and 21.0 kilopascals

Maximum Aromatics Percentage By Volume:

25.0

Distillation Point Percentage At Maximum Temp:

90-145 degrees c at 20pct, 110-190 degrees c at 50 pct and 245 degrees c at 90 pct

Maximum Distillation Residue Volume Percentage:

1.5

Specific Gravity Value At 15.56 Deg Celsius:

15.560

Copper Corrosion Classification Number:

1

Density Value:

Between 751.000 kilograms per cubic meter and 802.000 kilograms per cubic meter

Minimum Heat Of Combustion Value:

42.8 megajoules per kilogram

Maximum Distillation Loss Volume Percentage:

1.5

Density Temp:

15.0 degrees celsius

Supply Classification:

Bulk

Maximum Amount Of Existent Gum:

7.0

Test Data Document:

81348-astmd1655 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A090a0