

View Online at <https://aerobasegroup.com/nsn/9130-01-234-1737>

**Maximum Sulphur Content Percentage By Weight:**

0.3

**Freezing Point Maximum Temp:**

-50.0 degrees celsius

**Fuel Grade Classification:**

Kero/b

**Reid Vapor Pressure Rating:**

Between 14.0 kilopascals and 21.0 kilopascals

**Maximum Aromatics Percentage By Volume:**

25.0

**Distillation Point Percentage At Maximum Temp:**

90-145 degrees c at 20pct, 110-190 degrees c at 50 pct and 245 degrees c at 90 pct

**Maximum Distillation Residue Volume Percentage:**

1.5

**Specific Gravity Value At 15.56 Deg Celsius:**

15.560

**Copper Corrosion Classification Number:**

1

**Density Value:**

Between 751.000 kilograms per cubic meter and 802.000 kilograms per cubic meter

**Minimum Heat Of Combustion Value:**

42.8 megajoules per kilogram

**Maximum Distillation Loss Volume Percentage:**

1.5

**Density Temp:**

15.0 degrees celsius

**Supply Classification:**

Bulk

**Maximum Amount Of Existent Gum:**

7.0

**Test Data Document:**

81348-astmd1655 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A090a0