

View Online at <https://aerobasegroup.com/nsn/9130-01-234-1738>

Maximum Sulphur Content Percentage By Weight:

0.3

Freezing Point Maximum Temp:

-50.0 degrees fahrenheit

Fuel Grade Classification:

Jet a-1

Viscosity At Rated Temp:

8.00 -20 degrees celsius

Maximum Aromatics Percentage By Volume:

20.0

Distillation Point Percentage At Maximum Temp:

204.4degcelsiusat1090percent

Specific Gravity Value At 15.56 Deg Celsius:

0.8024

Copper Corrosion Classification Number:

1

Density Value:

Between 775.00 kilograms per cubic meter and 840.00 kilograms per cubic meter

Minimum Heat Of Combustion Value:

18400.0 british thermal units per pound

Maximum Distillation Loss Volume Percentage:

1.5

Minimum Flash Point And Test Method:

37.8 degrees celsius tag closed cup

Supply Classification:

Bulk

Maximum Amount Of Existent Gum:

7.0

Test Data Document:

81346-astmd1655 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A090a0