

View Online at <https://aerobasegroup.com/nsn/9130-01-287-2704>

Quantity Within Each Unit Package:

5.0 gallons

Maximum Sulphur Content Percentage By Weight:

0.4

Freezing Point Maximum Temp:

-46.0 degrees celsius

Fuel Grade Classification:

Jp-5

Viscosity At Rated Temp:

8.50 -20 degrees celsius

Maximum Aromatics Percentage By Volume:

25.0

Distillation Point Percentage At Maximum Temp:

300.0 degrees celsius at the fbp

Mandatory Additive:

Fsii and corrosion inhibitor

Nato Code Number:

F44

Maximum Distillation Residue Volume Percentage:

1.5

Copper Corrosion Classification Number:

1b

Density Value:

Between 0.788 kilograms per liter and 0.845 kilograms per liter

Err Default:

Err default

Minimum Heat Of Combustion Value:

42.6 megajoules per kilogram

Maximum Distillation Loss Volume Percentage:

1.5

Minimum Flash Point And Test Method:

60.0 degrees celsius pensky-martens closed cup

Density Temp:

15.0 degrees celsius

Supply Classification:

Packaged

Maximum Amount Of Existent Gum:

7.0

Specification Data:

81349-mil-t-5624 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A090a0