

View Online at <https://aerobasegroup.com/nsn/9130-01-305-5595>

**Maximum Sulphur Content Percentage By Weight:**

0.3

**Freezing Point Maximum Temp:**

-50.0 degrees celsius

**Fuel Grade Classification:**

Kero/b

**Reid Vapor Pressure Rating:**

Between 14.0 kilopascals and 21.0 kilopascals

**Maximum Aromatics Percentage By Volume:**

25.0

**Distillation Point Percentage At Maximum Temp:**

145.0 degrees c at 20.0 pct, 190.0 degrees c at 50.0 pct and 245.0 degrees c at 90.0 pct.

**Copper Corrosion Classification Number:**

1

**Density Value:**

Between 751.000 kilograms per cubic meter and 802.000 kilograms per cubic meter

**Minimum Heat Of Combustion Value:**

42.8 megajoules per kilogram

**Maximum Distillation Loss Volume Percentage:**

1.5

**Density Temp:**

15.0 degrees celsius

**Supply Classification:**

Bulk

**Maximum Amount Of Existent Gum:**

7.0

**Special Features:**

This product is applicable only to into-plane procurements/contracts in accordance with mil-std-1548 requirements.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A090a0