

View Online at <https://aerobasegroup.com/nsn/9130-01-373-0208>

**Maximum Sulphur Content Percentage By Weight:**

0.3

**Freezing Point Maximum Temp:**

-72.0 degrees fahrenheit

**Fuel Grade Classification:**

Jp-8

**Viscosity At Rated Temp:**

8.00 -20 degrees celsius

**Maximum Aromatics Percentage By Volume:**

25.0

**Distillation Point Percentage At Maximum Temp:**

205.0 degrees c at 10.0 pct and 300.0deg c at the end point

**Maximum Distillation Residue Volume Percentage:**

1.5

**Copper Corrosion Classification Number:**

1

**Density Value:**

Between 0.775 kilograms per liter and 0.840 kilograms per liter

**Err Default:**

Err default

**Minimum Heat Of Combustion Value:**

42.8 megajoules per kilogram

**Maximum Distillation Loss Volume Percentage:**

1.5

**Minimum Flash Point And Test Method:**

38.0 degrees celsius pensky-martens closed cup

**Density Temp:**

15.0 degrees celsius

**Supply Classification:**

Bulk

**Maximum Amount Of Existent Gum:**

7.0

**Special Features:**

Product is for national science foundation-sponsored antarctic fuels operations only

**Departure From Cited Document:**

Depressed freeze point

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A090a0