## NSN 9130-01-429-4563

Aviation Turbine Fuel - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/9130-01-429-4563

Maximum Sulphur Content Percentage By Weight:  0.3  Freezing Point Maximum Temp: -72.0 degrees fahrenheit  Fuel Grade Classification:  Jp-8  Viscosity At Rated Temp: 8.00 -20 degrees celsius  Maximum Aromatics Percentage By Volume: 25.0  Distillation Point Percentage At Maximum Temp: 205.0 degrees c at 10.0 pct and 300.0 degrees c at the end point.  Copper Corrosion Classification Number:
Freezing Point Maximum Temp: -72.0 degrees fahrenheit  Fuel Grade Classification:  Jp-8  Viscosity At Rated Temp: 8.00 -20 degrees celsius  Maximum Aromatics Percentage By Volume: 25.0  Distillation Point Percentage At Maximum Temp: 205.0 degrees c at 10.0 pct and 300.0 degrees c at the end point.  Copper Corrosion Classification Number:
-72.0 degrees fahrenheit  Fuel Grade Classification:  Jp-8  Viscosity At Rated Temp: 8.00 -20 degrees celsius  Maximum Aromatics Percentage By Volume: 25.0  Distillation Point Percentage At Maximum Temp: 205.0 degrees c at 10.0 pct and 300.0 degrees c at the end point.  Copper Corrosion Classification Number:
Fuel Grade Classification:  Jp-8  Viscosity At Rated Temp:  8.00 -20 degrees celsius  Maximum Aromatics Percentage By Volume:  25.0  Distillation Point Percentage At Maximum Temp:  205.0 degrees c at 10.0 pct and 300.0 degrees c at the end point.  Copper Corrosion Classification Number:
Jp-8  Viscosity At Rated Temp:  8.00 -20 degrees celsius  Maximum Aromatics Percentage By Volume:  25.0  Distillation Point Percentage At Maximum Temp:  205.0 degrees c at 10.0 pct and 300.0 degrees c at the end point.  Copper Corrosion Classification Number:
Viscosity At Rated Temp:  8.00 -20 degrees celsius  Maximum Aromatics Percentage By Volume:  25.0  Distillation Point Percentage At Maximum Temp:  205.0 degrees c at 10.0 pct and 300.0 degrees c at the end point.  Copper Corrosion Classification Number:
8.00 -20 degrees celsius  Maximum Aromatics Percentage By Volume: 25.0  Distillation Point Percentage At Maximum Temp: 205.0 degrees c at 10.0 pct and 300.0 degrees c at the end point.  Copper Corrosion Classification Number:
Maximum Aromatics Percentage By Volume: 25.0  Distillation Point Percentage At Maximum Temp: 205.0 degrees c at 10.0 pct and 300.0 degrees c at the end point.  Copper Corrosion Classification Number:
25.0  Distillation Point Percentage At Maximum Temp: 205.0 degrees c at 10.0 pct and 300.0 degrees c at the end point.  Copper Corrosion Classification Number:
Distillation Point Percentage At Maximum Temp:  205.0 degrees c at 10.0 pct and 300.0 degrees c at the end point.  Copper Corrosion Classification Number:
205.0 degrees c at 10.0 pct and 300.0 degrees c at the end point.  Copper Corrosion Classification Number:
Copper Corrosion Classification Number:
1
Dencity Value:
Density Value:  Between 0.775 kilograms per liter and 0.840 kilograms per liter
Minimum Heat Of Combustion Value:
18400.0 british thermal units per pound
Maximum Distillation Loss Volume Percentage:
1.5
Minimum Flash Point And Test Method:
38.0 degrees celsius pensky-martens closed cup
Density Temp:
15.0 degrees celsius
Supply Classification:
Bulk
Maximum Amount Of Existent Gum:
7.0
Special Features:
This nsn is for af use only to account for purchases of arctic jp8at mcmurdo, antarctica
Specification Or Standard:
In8 code
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig:
A090a0