

View Online at <https://aerobasegroup.com/nsn/9130-01-527-7832>

**Maximum Sulphur Content Percentage By Weight:**

0.20

**Freezing Point Maximum Temp:**

-47.0 degrees celsius

**Fuel Grade Classification:**

Jp-8

**Viscosity At Rated Temp:**

8.00 -20 degrees celsius

**Maximum Aromatics Percentage By Volume:**

25.0

**Distillation Point Percentage At Maximum Temp:**

205.0 degrees c at 10.0 pct & 300.0 degrees c at the end point

**Copper Corrosion Classification Number:**

1

**Density Value:**

Between 0.775 kilograms per liter and 0.840 kilograms per liter

**Minimum Heat Of Combustion Value:**

42.8 megajoules per kilogram

**Maximum Distillation Loss Volume Percentage:**

1.5

**Minimum Flash Point And Test Method:**

38.0 degrees celsius pensky-martens closed cup

**Density Temp:**

15.0 degrees celsius

**Supply Classification:**

Bulk

**Maximum Amount Of Existent Gum:**

7.0

**Special Features:**

THIS-NS-NIS-APPL

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A090a0