

View Online at <https://aerobasegroup.com/nsn/9140-00-419-0450>

**Quantity Within Each Unit Package:**

475.000 gallons

**Lubricity At 6 Designator Deg Centigrade:**

520.0 micrometers

**Maximum Ash Content Percentage By Weight:**

0.01

**Maximum Sulphur Content Percentage By Weight:**

0.5

**Minimum Cetane Classification Number:**

45

**Maximum Cloud Point Temp:**

-25.0 degrees fahrenheit

**Fuel Grade Classification:**

Diesel, low sulfur, arctic

**Viscosity At Rated Temp:**

1.40 100 degrees fahrenheit or 3.00 100 degrees fahrenheit

**Maximum Pour Point:**

-35.0 degrees fahrenheit

**Maximum Carbon Residue Content Percentage By Weight And Test Method:**

0.15 ramsbottom

**Minimum Flash Point And Test Method:**

100.0 degrees fahrenheit pensky-martens closed cup

**Special Features:**

Packaged in 500 gal drum, fsn8110-824-1444

**Specification Or Standard:**

Df-1 grade

**Departure From Cited Designator:**

As modified by special features and unit package quantity

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A090a0