

View Online at <https://aerobasegroup.com/nsn/9140-01-235-2882>

**Maximum Ash Content Percentage By Weight:**

0.10

**Maximum Sulphur Content Percentage By Weight:**

4.00

**Viscosity At Rated Temp:**

380.00 50 degrees celsius

**Maximum Pour Point:**

24.0 degrees celsius

**Maximum Carbon Residue Content Percentage By Weight And Test Method:**

16.0 conradson

**Density Value:**

0.991 grams per milliliter

**Minimum Flash Point And Test Method:**

60.0 degrees celsius pensky-martens closed cup

**Density Temp:**

15.0 degrees celsius

**Supply Classification:**

Bulk

**Err Default:**

Err default

**Special Features:**

Used for bunkers purchase program only. Vanadium 300 ppm, aluminium 300 ppm, sediment 0.15, water 1.00; fuel grade: naval 20 pour

**Test Data Document:**

81348-ifo380 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A090a0