

View Online at <https://aerobasegroup.com/nsn/9140-01-412-1311>

**Maximum Ash Content Percentage By Weight:**

0.01

**Maximum Sulphur Content Percentage By Weight:**

0.05

**Minimum Cetane Classification Number:**

40

**Fuel Grade Classification:**

Df1 low sulfur

**Viscosity At Rated Temp:**

1.30 40 degrees celsius and 2.90 40 degrees celsius

**Distillation Point Percentage At Maximum Temp:**

288.0 degrees c at 90.0 percent recovered and 330.0 degrees c at end point

**Maximum Carbon Residue Content Percentage By Weight And Test Method:**

0.15 ramsbottom

**Mandatory Additive:**

Product must contain visible evidence of red dye. 164 - which is composed of alkyl derivatives of azo benzene/azo naphthol.

**Maximum Distillation Residue Volume Percentage:**

3.0

**Copper Corrosion Classification Number:**

3

**Minimum Flash Point And Test Method:**

38.00 degrees celsius pensky-martens closed cup

**Supply Classification:**

Bulk

**Special Features:**

This red dyed winter diesel fuel is untaxed and is for off-highway use only.

**Specification Or Standard:**

Dlw code

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A090a0