

View Online at <https://aerobasegroup.com/nsn/9140-01-456-9443>

**Lubricity At 6 Designator Deg Centigrade:**

520.0 micrometers

**Maximum Ash Content Percentage By Weight:**

0.01

**Maximum Sulphur Content Percentage By Weight:**

0.5

**Minimum Cetane Classification Number:**

45

**Maximum Cloud Point Temp:**

20.0 degrees fahrenheit

**Fuel Grade Classification:**

Diesel, low sulfur, arctic

**Viscosity At Rated Temp:**

2.00 100 degrees fahrenheit or 4.30 100 degrees fahrenheit

**Maximum Pour Point:**

10.0 degrees fahrenheit

**Maximum Carbon Residue Content Percentage By Weight And Test Method:**

0.35 ramsbottom

**Nato Code Number:**

F54

**Minimum Flash Point And Test Method:**

125.0 degrees fahrenheit pensky-martens closed cup

**Supply Classification:**

Bulk

**Special Features:**

This product is for ship's bunkers fuel only. Applies to the following locations only baltimore md fort meade cape girardeau mo st louis mo

**Specification Or Standard:**

Df-2 grade

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A090a0