

View Online at <https://aerobasegroup.com/nsn/9140-01-534-3332>

Lubricity At 6 Designator Deg Centigrade:

460.0 micrometers

Maximum Sulphur Content Percentage By Weight:

0.003

Minimum Cetane Classification Number:

45

Fuel Grade Classification:

Diesel, ultra-low sulfur

Viscosity At Rated Temp:

1.90 40 degrees celsius and 5.50 40 degrees celsius

Maximum Pour Point:

-30.0 degrees celsius

Distillation Point Percentage At Maximum Temp:

330 degrees c at 90 percent

Maximum Carbon Residue Content Percentage By Weight And Test Method:

0.1 conradson

Copper Corrosion Classification Number:

1

Minimum Flash Point And Test Method:

45.0 degrees celsius pensky-martens closed cup

Supply Classification:

Bulk

Special Features:

30ppm, maximum sulfur requirements in accordance with the clean air quality preservation act. Sulfur ppm maximum 30. Densi type 15 degrees c (kg/m³) 815-855, kinematic viscosity. Water and sediment content, vol %, maximum 0.02, ash, wt% maximum 0.02; polyaromatic wt%, maximum 11. Winter grade. Maximum per desc procurement clause c16.26-5, fuel oil, diesel (pc&s) (korea).

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A090a0