

View Online at <https://aerobasegroup.com/nsn/9150-01-496-1943>

Fatty Material Type:

Any acceptable

Basic Ingredient:

Any acceptable

Service Characteristics:

Antifoam and antiwear and corrosion resistive

Quantity Within Each Unit Package:

55.000 gallons

Viscosity At Rated Temp:

5.70 210 degrees fahrenheit and 7.50 210 degrees fahrenheit

Maximum Pour Point:

-25.0 degrees fahrenheit

Minimum Flash Point And Test Method:

400.0 degrees fahrenheit cleveland open cup

Environmental Attribute Code:

Comprehensive procurement guideline - vehicular products - re-refined lubricating oils

Special Features:

Closed-loop re-refined oil 10 grade; fatty materail type; per service manuals required for 2004 chvy express, gmc savana van, vol1, pg 0-43, fig 561515, 2004 chvy silverado, gmc sierra/sierra denali truck service manual vol1, pg 055, fig 929256; john deere model 644 front end loader, tech manual tm1413, pg. I-iv-2 fig t7396bk, 1998 chrysler corporation ram truck 1500-3500 services, service manual pg 9-4, fig 900cedd5, and additional assigned base vehicles.

Supplementary Features:

Api engine service classification cd

Specification Or Standard:

10 grade

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A41600