

View Online at <https://aerobasegroup.com/nsn/9150-01-496-1943>

**Fatty Material Type:**

Any acceptable

**Basic Ingredient:**

Any acceptable

**Service Characteristics:**

Antifoam and antiwear and corrosion resistive

**Quantity Within Each Unit Package:**

55.000 gallons

**Viscosity At Rated Temp:**

5.70 210 degrees fahrenheit and 7.50 210 degrees fahrenheit

**Maximum Pour Point:**

-25.0 degrees fahrenheit

**Minimum Flash Point And Test Method:**

400.0 degrees fahrenheit cleveland open cup

**Environmental Attribute Code:**

Comprehensive procurement guideline - vehicular products - re-refined lubricating oils

**Special Features:**

Closed-loop re-refined oil 10 grade; fatty materail type; per service manuals required for 2004 chvy express, gmc savana van, vol1, pg 0-43, fig 561515, 2004 chvy silverado, gmc sierra/sierra denali truck service manual vol1, pg 055, fig 929256; john deere model 644 front end loader, tech manual tm1413, pg. I-iv-2 fig t7396bk, 1998 chrysler corporation ram truck 1500-3500 services, service manual pg 9-4, fig 900cedd5, and additional assigned base vehicles.

**Supplementary Features:**

Api engine service classification cd

**Specification Or Standard:**

10 grade

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A41600