

View Online at <https://aerobasegroup.com/nsn/9320-00-010-3985>

**Cross Sectional Shape:**

Rectangular

**Fabrication Method:**

Solid and cellular, exploded

**Nonmetallic Hardness Rating:**

55.0 shore durometer a and 65.0 shore durometer a

**Min. Tensile Strength (psi):**

1500 pounds per square inch

**Tempurature Rating:**

-55.0 degrees celsius and 100.0 degrees celsius

**Length:**

Between 7.719 inches and 7.781 inches

**Surface Condition:**

Smooth both sides

**Cross-sectional Height:**

Between 2.344 inches and 2.406 inches

**Cross-sectional Width:**

Between 0.219 inches and 0.281 inches

**Strengthening Feature Material:**

Rubber, mil-std-670, type r, style o, grade ro11a1bf1

**Environmental Protection:**

Compression and heat resistant and high temperature and low temperature

**Strengthening Feature:**

Backing

**External Strengthening Feature Location:**

Both sides

**Special Features:**

Skin on all surfaces 0.015 in. Min, 0.035in. Maximum thick

**Color:**

Black both sides

**Material:**

Rubber, mil-std-670, type r, style o, grade ro11a1bf1

**Material:**

Rubber butadiene-styrene class sbr or rubber chloroprene class cr

**Material Specification:**

Mil-std-670, type r, style o, grade ro11a1bf1 military specification single material response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A26800

**Mil-std (military Standard):**

Mil-std-670 spec.