NSN 9320-00-141-7166

Cellular Rubber Sheet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/9320-00-141-7166

Cellular, exploded Width: Between 23.750 inches and 24.250 inches Tempurature Rating: -41.0 degrees celsius Thickness: Between 0.469 inches and 0.531 inches Length: Between 23.750 inches and 24.250 inches Surface Condition: Smooth both sides Environmental Protection: Low temperature Material: Rubber, cellular, mil-r-6130, type 1, grade b, condition medium Material: Rubber butadiene-styrene class sbr Specification Or Standard: Medium condition and b grade and i type Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A26800 Mil-std (military Standard): Mil-r-6130 spec.	Fabrication Mathed
Width: Between 23.750 inches and 24.250 inches Tempurature Rating: -41.0 degrees celsius Thickness: Between 0.469 inches and 0.531 inches Length: Between 23.750 inches and 24.250 inches Surface Condition: Smooth both sides Environmental Protection: Low temperature Material: Rubber, cellular, mil-r-6130, type 1, grade b, condition medium Material: Rubber butadiene-styrene class sbr Specification Or Standard: Medium condition and b grade and i type Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A26800 Mil-std (military Standard):	Fabrication Method:
Between 23.750 inches and 24.250 inches Tempurature Rating: -41.0 degrees celsius Thickness: Between 0.469 inches and 0.531 inches Length: Between 23.750 inches and 24.250 inches Surface Condition: Smooth both sides Environmental Protection: Low temperature Material: Rubber, cellular, mil-r-6130, type 1, grade b, condition medium Material: Rubber butadiene-styrene class sbr Specification Or Standard: Medium condition and b grade and i type Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A26800 Mil-std (military Standard):	Cellular, exploded
Tempurature Rating: -41.0 degrees celsius Thickness: Between 0.469 inches and 0.531 inches Length: Between 23.750 inches and 24.250 inches Surface Condition: Smooth both sides Environmental Protection: Low temperature Material: Rubber, cellular, mil-r-6130, type 1, grade b, condition medium Material: Rubber butadiene-styrene class sbr Specification Or Standard: Medium condition and b grade and i type Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A26800 Mil-std (military Standard):	Width:
-41.0 degrees celsius Thickness: Between 0.469 inches and 0.531 inches Length: Between 23.750 inches and 24.250 inches Surface Condition: Smooth both sides Environmental Protection: Low temperature Material: Rubber, cellular, mil-r-6130, type 1, grade b, condition medium Material: Rubber butadiene-styrene class sbr Specification Or Standard: Medium condition and b grade and i type Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A26800 Mil-std (military Standard):	Between 23.750 inches and 24.250 inches
Thickness: Between 0.469 inches and 0.531 inches Length: Between 23.750 inches and 24.250 inches Surface Condition: Smooth both sides Environmental Protection: Low temperature Material: Rubber, cellular, mil-r-6130, type 1, grade b, condition medium Material: Rubber butadiene-styrene class sbr Specification Or Standard: Medium condition and b grade and i type Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A26800 Mil-std (military Standard):	Tempurature Rating:
Between 0.469 inches and 0.531 inches Length: Between 23.750 inches and 24.250 inches Surface Condition: Smooth both sides Environmental Protection: Low temperature Material: Rubber, cellular, mil-r-6130, type 1, grade b, condition medium Material: Rubber butadiene-styrene class sbr Specification Or Standard: Medium condition and b grade and i type Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A26800 Mil-std (military Standard):	-41.0 degrees celsius
Length: Between 23.750 inches and 24.250 inches Surface Condition: Smooth both sides Environmental Protection: Low temperature Material: Rubber, cellular, mil-r-6130, type 1, grade b, condition medium Material: Rubber butadiene-styrene class sbr Specification Or Standard: Medium condition and b grade and i type Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A26800 Mil-std (military Standard):	Thickness:
Between 23.750 inches and 24.250 inches Surface Condition: Smooth both sides Environmental Protection: Low temperature Material: Rubber, cellular, mil-r-6130, type 1, grade b, condition medium Material: Rubber butadiene-styrene class sbr Specification Or Standard: Medium condition and b grade and i type Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A26800 Mil-std (military Standard):	Between 0.469 inches and 0.531 inches
Surface Condition: Smooth both sides Environmental Protection: Low temperature Material: Rubber, cellular, mil-r-6130, type 1, grade b, condition medium Material: Rubber butadiene-styrene class sbr Specification Or Standard: Medium condition and b grade and i type Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A26800 Mil-std (military Standard):	Length:
Smooth both sides Environmental Protection: Low temperature Material: Rubber, cellular, mil-r-6130, type 1, grade b, condition medium Material: Rubber butadiene-styrene class sbr Specification Or Standard: Medium condition and b grade and i type Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A26800 Mil-std (military Standard):	Between 23.750 inches and 24.250 inches
Environmental Protection: Low temperature Material: Rubber, cellular, mil-r-6130, type 1, grade b, condition medium Material: Rubber butadiene-styrene class sbr Specification Or Standard: Medium condition and b grade and i type Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A26800 Mil-std (military Standard):	Surface Condition:
Low temperature Material: Rubber, cellular, mil-r-6130, type 1, grade b, condition medium Material: Rubber butadiene-styrene class sbr Specification Or Standard: Medium condition and b grade and i type Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A26800 Mil-std (military Standard):	Smooth both sides
Material: Rubber, cellular, mil-r-6130, type 1, grade b, condition medium Material: Rubber butadiene-styrene class sbr Specification Or Standard: Medium condition and b grade and i type Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A26800 Mil-std (military Standard):	Environmental Protection:
Rubber, cellular, mil-r-6130, type 1, grade b, condition medium Material: Rubber butadiene-styrene class sbr Specification Or Standard: Medium condition and b grade and i type Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A26800 Mil-std (military Standard):	Low temperature
Material: Rubber butadiene-styrene class sbr Specification Or Standard: Medium condition and b grade and i type Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A26800 Mil-std (military Standard):	Material:
Rubber butadiene-styrene class sbr Specification Or Standard: Medium condition and b grade and i type Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A26800 Mil-std (military Standard):	Rubber, cellular, mil-r-6130, type 1, grade b, condition medium
Specification Or Standard: Medium condition and b grade and i type Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A26800 Mil-std (military Standard):	Material:
Medium condition and b grade and i type Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A26800 Mil-std (military Standard):	Rubber butadiene-styrene class sbr
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A26800 Mil-std (military Standard):	Specification Or Standard:
N/a Unit Of Measure: Demilitarization: No Fiig: A26800 Mil-std (military Standard):	Medium condition and b grade and i type
Unit Of Measure: Demilitarization: No Fiig: A26800 Mil-std (military Standard):	Shelf Life:
Demilitarization: No Fiig: A26800 Mil-std (military Standard):	N/a
No Fiig: A26800 Mil-std (military Standard):	Unit Of Measure:
No Fiig: A26800 Mil-std (military Standard):	
Fiig: A26800 Mil-std (military Standard):	Demilitarization:
A26800 Mil-std (military Standard):	No
Mil-std (military Standard):	Fiig:
	A26800
Mil-r-6130 spec.	Mil-std (military Standard):
	Mil-r-6130 spec.